

# 3906 SERIES

## 23" x 3RU BATTERY BREAKER PANEL +24V or -48V | 500A

### **DESCRIPTION**

UNIPOWER's 3906 Series provides a compact battery disconnect solution with high-capacity, current-interrupting breakers.

The 3906 Battery Breaker Panel can be configured for +24V or -48V operation and has a maximum capacity of 500 amps.

Up to 13 breakers rated from 5A to 100A can be installed, subject to the overall capacity not being exceeded.

The 3906 Battery Breaker Panel incorporates a 500A return busbar.

### **FEATURES**

- ◆ 3RU High: 5.22"
- ♦ 23-Inch Rack Mounting
- Current Capacity: 500A
- ◆ Operating Voltage:+24 or -48VDC
- ♦ 13 Breakers 5A to 100A
- ♦ Integral Return Bar
- LED Alarm Indicator
- ◆ Form C Relay Contacts

THREE YEAR WARRANTY



### STANDARD CONFIGURATIONS

VOLTAGE	ALARM	BREAKER POSITIONS	PART NUMBER
-48VDC	Yes	13	111-3906-48
+24VDC	res		111-3906-25

#### **AVAILABLE BREAKERS**

PART NUMBER	AMPS	PART NUMBER	AMPS
274-3811-05	5A	274-3811-40	40A
274-3811-10	10A	274-3811-50	50A
274-3811-15	15A	274-3811-60	60A
274-3811-20	20A	274-3811-70	70A
274-3811-25	25A	274-3811-80	80A
274-3811-30	30A	274-3811-90	90A
274-3811-35	35A	274-3811-100	100A

Note: Breakers must be ordered separately.



# **SPECIFICATIONS**


Typical at 25°C Unless Otherwise Noted.

INPUT / OUTPUT	ANG with Alama Cartain
Breaker Type Breaker Current Rating Breaker Interrupt Rating	AMI WILL Alarm Contact
Breaker Current Rating	5A to 100A
Breaker Interrupt Rating	IUKAIC
Panel Capacity	500A
Breaker Configuration	13 Breakers
Panel Capacity Breaker Configuration Alarm Fuses	GMT (recommended 0.5A)
Voltage	
-48V Nominal	42-60VDC
-48V Nominal +24V Nominal	21-30VDC
ALARMS	
Alarm Indicator	Red LED
LED Status	OFF = Normal
	ON = Alarm
Alarm Relay	Form C


ENVIRONMENTAL Operating Temp. RangeStorage Temp. RangeHumidity	10°C to +70°C 40°C to + 85°C 
MECHANICAL SPECIFICATIONS	Ctool
Panel MaterialFinish	Douglar Coat Cray
Dimensions, Inches (mm)	Powder Coat Gray
,	
Weight Mounting	(132.6 x 584.2 x 190.3)
Weight	16.0 lbs. (7.3 kg.)
Mounting	23" x 3RU
CONNECTIONS  Bus Bar ConnectionsAr  Breaker Connections	

Alarm Connections .......Compression/Screw Terminals

### **SCHEMATIC**





### ALARM BOARD WIRING






### **OVERVIEW & DIMENSIONS**





# REAR VIEW (as seen from the back)



© 2021 UNIPOWER LLC

be correct at time of publication and Unipower LLC accepts no responsibility for consequences from printing errors or inaccuracies. All specifications subject to change without notice.