

EASYMOD® AD-070U

AC INPUT / ITE APPROVED

70 WATT POWER PLATFORM

5.00 x 3.00 x 1.00" | 127.0 x 76.2 x 25.4mm



DESCRIPTION

UNIPOWER's **EASYMOD® AD-070U SERIES** is a 70 Watt Power Supply platform with both standard and configurable models featuring output voltage(s) that can be quickly configured to order while maintaining all international safety approvals.

These power supplies are available with Universal AC Input and single or quad output configurations ranging from 1.5 to 48 VDC. The AD-070U feature an industry-standard footprint, international safety approvals, Class B emissions; and -20 ~ +70°C operation (see derating).

EASYMOD® UPGRADES include a multitude of output voltage configurations, extended temperature operating range, isolated outputs, attached wire harnesses and much, much more. All these modifications are available without any impact on safety approvals to reduce both development cost and time to market.

FEATURES

- ◆ Universal AC Input Range (90-264 VAC)
- ◆ Industry-Standard 3" x 5" Footprint
- ◆ 1 or 4 Outputs configurable from 1.5-48VDC
- ◆ International Safety Approvals
- ◆ >500k Hours MTBF, Demonstrated
- ◆ Optional -40°C Guaranteed Start-Up
- ◆ Double Sided PC Board



Contact UNIPOWER to discuss your application and define the right part number for your specific application:

Tel: +1-954-905-1070

Email: the.power.solution@unipowerco.com



FIVE YEAR WARRANTY

INTERNATIONAL STANDARDS

UL/cUL 60950-1 2nd Ed.
 EN60950-1 2nd Ed.
 CB Report, IEC60950-1
 CE Mark (LVD)

www.unipowerco.com

NORTH AMERICA CALL: +1-954-905-1071 • LATIN AMERICA CALL: +1-954-905-1078 • EUROPE CALL: +44 1903 768200

For the DC input version see [DCMOD AD-070D](#) datasheet

For the Medical Approved version see [MEDIMOD AD-070UM](#) datasheet

“IF WHAT YOU SEE IS WHAT YOU DON’T WANT, IT CAN EASILY BE CHANGED.” The EASYMOD® family of switching power supplies has been designed with two precepts; (1) the laws of physics are immutable, and (2) the satisfaction of customer requirements and needs is paramount.

A host of modifications, only some of which are listed below, can and will be performed on products for customer programs requiring as few as 250 units per year. These “mods” are available at nominal premium (if any), normally without non-recurring engineering costs (although a one time documentation fee may be incurred), and usually with all safety agency approvals in place. This minimizes both product development cost and new product time to market. Effectively, EASYMODs® allow small program requirements the luxury of costly custom power supply designs.

TYPICAL MODIFICATIONS

- Unique Output Combinations from 1.5 to >48 volts
- Isolated Outputs
- Low Output Ripple and Noise
- Extended Temperature Operating Range
- -40°C Start-Up
- Zero Load Operation

FLEXIBLE OUTPUT CONFIGURATION GUIDELINES

with 90-264 VAC Input and -20-50°C Operation

Single Output Capabilities

OUTPUT CURRENT	1.5~3.3V	5V	12V	15V	24V	48V
MINIMUM	0A	0A	0A	0A	0A	0A
CONVECTION ⁽³⁾	10A	10A	4.2A	3.3A	2.1A	1.1A
15 CFM AIR ⁽⁴⁾	14A	14A	5.9A	4.6A	3.0A	1.4A
PEAK ⁽⁵⁾	15A	15A	6.5A	5.0A	3.5A	1.5A

Multiple Output Capabilities

OUTPUT	DC OUTPUT	MIN	CON ⁽³⁾	AIR ⁽⁴⁾	PEAK ^(4, 5)
V1	1.5 ~ 48V ⁽⁷⁾	0.80A	8.0A	12.0A	13.0A
V2	1.5 ~ 48V ⁽⁸⁾	0.40A	4.0A	5.0A	6.0A
V3	1.5 ~ 48V ⁽⁸⁾	0.40A	4.0A	5.0A	6.0A
V4	1.5 ~ 48V ⁽⁸⁾	0.20A	2.0A	2.5A	3.0A

(1) Full power out on V3-V4 with minimal V1 and V2 loading—Option.
 (2) 10% minimum load for stated regulation on multiple O/P units.
 (3) Convection cooling.
 (4) 15 CFM forced air cooling, conditions.
 (5) 30 seconds maximum duration.
 (6) Most output combinations from 1.5 to 48 Volts possible; up to maximum rated Current / Power...Consult UNIPOWER.

(7) Specify 0.1V increments.
 (8) Specific output voltage is current dependent.
 (9) Regulation may degrade under some output Consult UNIPOWER.
 (10) Consult UNIPOWER for Model #.
 (11) For outputs >48 Volts, consult UNIPOWER.
 (12) 10% minimum of marked rating.

Contact UNIPOWER to discuss your application and define the right part number for your specific application:

Call: +1-954-905-1070 • Email: the.power.solution@unipowerco.com

For the DC input version see [DCMOD AD-070D](#) datasheet | For the Medical Approved version see [MEDIMOD AD-070UM](#) datasheet.

SPECIFICATIONS

Typical at Nominal Line, Full Load and 25°C Unless Otherwise Noted.

INPUT

Input Voltage Range.....	90-264 VAC
Frequency.....	47-63Hz
Power Factor.....	EN61000-3-2 Amendment 14 Compliant
Inrush Current.....	.35A Max (cold start)
Input Current @ 115VAC.....	2.5A max
Fusing.....	3.15A / 250VAC

OUTPUT

Output Power	50W Convection / 70W with 15 CFM Airflow
Hold-up Time	16mSec
Efficiency.....	70% Typical
Adjustment Range (V1 Only).....	±5%
Ripple / Noise, max.....	1% pk-pk max
Line Regulation.....	Max ±0.2%
Load Regulation @ 60% ±40% Full Load	
V1.....	±3% max
V2-V4.....	±5% max
Cross Regulation @ 60% ± 40% Full Load	
V1: Change in V2 - V4.....	±0.5%
V2 - V4: Change in V1 @75 ±25% F/L	±5% max
Overvoltage Protection (V1 Only).....	>125% (Latch Off)
Power Limit	>120% (Auto-Recovery)
Overshoot (all outputs).....	10% max
Response Time.....	500 µSec (25-75% step load)
Switching Frequency.....	60KHz (typical)

ENVIRONMENTAL

Operating Temp. Range	-20°C to +50°C (Full Load)
	Consult factory for -40°C Guaranteed Start-Up and Industrial Temperature Range options
Output Current Derating	2.5%/°C, 50°C to 70°C
Storage Temp. Range	-40°C to + 85°C
Humidity.....	5% to 95%, Non-Condensing
MTBF, Demonstrated	>500,000 Hours
Cooling	15 CFM Airflow for Full Power
Immunity.....	EN61000-4-2; -3; -4; -5; -6; -8; -11
Altitude.....	10,000 feet

PHYSICAL SPECIFICATIONS

Case Dimensions	5.00 x 3.00 x 1.00" / 127 x 76.2 X 25.4mm
Weight	0.6 lbs. (0.27 kg.)
Vibration from 10 - 55Hz.....	1.0G Peak
	(3 orthogonal axes @ 1 octave/min, 5 minute dwell @ 4 major resonances)

SAFETY STANDARDS

UL60950-1 2nd Ed., EN60950-1 2nd Ed., CB REPORT (IEC 60950-1), CE MARK (LVD)

EMI STANDARDS

FCC Class B & VDE Class B, CISPR 22: EN 55022 Class B

OUTLINE DRAWING

CONNECTOR 1

(MOLEX#09-65-2058 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3051)

PIN1.....	GROUND
PIN2.....	KEY
PIN3.....	NEUTRAL
PIN4.....	KEY
PIN5.....	LINE

CONNECTOR 2 (single output)

(MOLEX#09-65-2088 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3081)

PIN1	V1
PIN2	V1
PIN3.....	V1
PIN4.....	RET
PIN5.....	RET
PIN6.....	RET
PIN7.....	NC
PIN8.....	NC

CONNECTOR 2 (multi-output)

(MOLEX#09-65-2088 OR EQUIVALENT;
MATING CONNECTOR= MOLEX#09-50-3081)

PIN1	V2
PIN2	V1
PIN3.....	V1
PIN4.....	RET
PIN5.....	RET
PIN6.....	V3
PIN7.....	V4
PIN8.....	V4 RET

