

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)  
CB SCHEME**
**CB TEST CERTIFICATE**

Product

Component DC-DC Power Supply

Name and address of the applicant

UNIPower L L C  
210 N UNIVERSITY DR, SUITE 700  
CORAL SPRINGS FL 33065  
UNITED STATES

Name and address of the manufacturer

UNIPower L L C  
210 N UNIVERSITY DR, SUITE 700  
CORAL SPRINGS FL 33065  
UNITED STATES

Name and address of the factory

ULTRAPOWER TECHNOLOGY INC  
7TH FL 6 LANE 497 CHUNG CHENG RD HSIN TIEN DIST NEW  
TAIPEI 231  
TAIWAN

*Note: When more than one factory, please report on page 2*
☐ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)

None

Type of Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

AG-350D-24XY-Z, AG-350D-48XY-Z  
See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN 60950-1:2006 / A11:2009 / A1:2010 / A12:2011 / A2:2013; National Differences specified in the CB Test Report.

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005/AMD1:2009, IEC 60950-1:2005/AMD2:2013, IEC 60950-1:2005

As shown in the Test Report Ref. No. which forms part of this Certificate

E147630-A6001-CB-1 issued on 2020-05-14

This CB Test Certificate is issued by the National Certification Body



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2020-05-14

Signature:

Jolanta M. Wroblewska



Ref. Certif. No.

**US-35780-UL**

**Model Details:**

AG-350D-24XY-Z, AG-350D-48XY-Z See model differences for the part number description.

**Ratings:**

**INPUT:**

AG-350D-24XY-Z Series: 18-36 V dc, 30 A

AG-350D-48XY-Z Series: 36-72 V dc, 20 A

**OUTPUTS:** AG-350D-XY-Z Series

Output	Volts (V dc)	Current (max)
V1	+/-1.5 to +/-48	60.0
V2	+/-1.5 to +/-48	32.0
V3	+/-1.5 to +/-48	7.0
V4	+/-1.5 to +/-48	14.0

Note: The combined total output power does not exceed 350W for 48V models and 298W for 24V models.

**Additional information (if necessary)**



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2020-05-14

Signature:

Jolanta M. Wroblewska