

EASYMOD® AG-350P
AC INPUT / ITE APPROVED
350 WATT POWER PLATFORM
8.00 x 4.50 x 2.00" / 203.2 x 114.3 x 50.8mm



DESCRIPTION

UNIPOWER's **EASYMOD® AG-350P SERIES** is a 350 Watt Power Supply platform with both standard and configurable models featuring output voltage(s) that can be quickly configured to order while maintaining all international safety approvals.

These power supplies are available with Universal AC Input and single or quad output configurations ranging from 1.5 to 48 VDC. The AG-350P feature an industry-standard footprint, medical safety approvals, Class B emissions; and -20 ~ +70°C operation (see derating).

EASYMOD® UPGRADES include a multitude of output voltage configurations, optional covers (with or without fan), extended temperature operating range, isolated outputs, attached wire harnesses and much, much more. All these modifications are available without any impact on safety approvals to reduce both development cost and time to market.

FEATURES

- ◆ Universal AC Input Range (90-264 VAC)
- ◆ Active PFC
- ◆ 1 or 4 Outputs configurable from 1.5-48VDC
- ◆ International Safety Approvals
- ◆ >500k Hours MTBF, Demonstrated
- ◆ Optional -40°C Guaranteed Start-Up
- ◆ Double Sided PC Board



Contact **UNIPOWER** to discuss
your application and define
the right part number for your
specific application:

Tel: +1-954-905-1070

Email: the.power.solution@unipowerco.com



FIVE YEAR WARRANTY

INTERNATIONAL STANDARDS

UL/cUL 60950-1 2nd Ed.
EN60950-1 2nd Ed.
CB Report, IEC60950-1
CE Mark (LVD)

For the DC input version see [DCMOD AG-350D](#) datasheet

For the Medical Approved version see [MEDIMOD AG-350PM](#) datasheet

www.unipowerco.com

NORTH AMERICA CALL: +1-954-905-1071 • LATIN AMERICA CALL: +1-954-905-1078 • EUROPE CALL: +44 1903 768200

"IF WHAT YOU SEE IS WHAT YOU DON'T WANT, IT CAN EASILY BE CHANGED." The EASYMOD® family of switching power supplies has been designed with two precepts; (1) the laws of physics are immutable, and (2) the satisfaction of customer requirements and needs is paramount.

A host of modifications, only some of which are listed below, can and will be performed on products for customer programs requiring as few as 250 units per year. These "mods" are available at nominal premium (if any), normally without non-recurring engineering costs (although a one time documentation fee may be incurred), and usually with all safety agency approvals in place. This minimizes both product development cost and new product time to market. Effectively, EASYMODs® allow small program requirements the luxury of costly custom power supply designs.

TYPICAL MODIFICATIONS

- Unique Output Combinations from 1.5 to >48 volts
- Power Fail / Power Good Signals
- Enable / Inhibit
- Isolated Outputs
- Low Output Ripple and Noise
- Cover & Fan Assembly
- Extended Temperature Operating Range
- -40°C Start-Up
- Zero Load Operation
- Remote Sense
- Remote On / Off

FLEXIBLE OUTPUT CONFIGURATION GUIDELINES

with 90-264 VAC Input and -20-50°C Operation

Single Output Capabilities

OUTPUT CURRENT	1.5~3.3V	5V	12V	15V	24V	48V
MINIMUM	0A	0A	0A	0A	0A	0A
CONVECTION ⁽³⁾	30A	30A	16.6A	13.3A	8.3A	4.2A
30 CFM AIR ⁽⁴⁾	60A	60A	29A	23A	14.5A	7.25A
PEAK ⁽⁵⁾	65A	65A	31A	25A	16A	18A

Multiple Output Capabilities

OUTPUT	DC OUTPUT	MIN	CON ⁽³⁾	AIR ⁽⁴⁾	PEAK ^(4, 5)
V1	1.5 ~ 48V ⁽⁷⁾	4.0A ^(2, 13)	40A	60A	65A
V2	1.5 ~ 48V ⁽⁸⁾	1.7A ^(2, 13)	17A	32A	35A
V3	1.5 ~ 48V ⁽⁸⁾	0.5A ^(2, 13)	5A	7A	10A
V4	1.5 ~ 48V ⁽⁸⁾	1.1A ^(2, 13)	11A	14A	18A

(1) Full power out on V3-V4 with minimal V1 and V2 loading—Option.
 (2) 10% minimum load for stated regulation on multiple O/P units.
 (3) Convection cooling.
 (4) 30 CFM forced air cooling conditions.
 (5) 30 seconds maximum duration.
 (6) Most output combinations from 1.5 to 48 Volts possible; up to maximum rated Current / Power...Consult UNIPOWER.

(7) Specify 01V increments.
 (8) Specific output voltage is current dependent.
 (9) Regulation may degrade under some output Consult UNIPOWER.
 (10) Consult UNIPOWER for Model #.
 (11) For outputs >48 Volts, consult UNIPOWER.
 (12) Cover and custom sheet metal available.
 (13) 10% minimum of marked rating

Contact UNIPOWER to discuss your application and define the right part number for your specific application:

Call: +1-954-905-1070 • Email: the.power.solution@unipowerco.com

For the DC input version see [DCMOD AG-350D](#) datasheet | For the Medical Approved version see [MEDIMOD AG-350PM](#) datasheet.

SPECIFICATIONS

Typical at Nominal Line, Full Load and 25°C Unless Otherwise Noted.

INPUT

Input Voltage Range Options	90-264 VAC
Frequency	47-63Hz
Power Factor	EN61000-3-2 Compliant
Inrush Current	50A Max (cold start)
Input Current @ 115VAC	6.0A max
Fusing	8A / 250VAC

OUTPUT

Output Power	200W Convection / 350W with 30 cfm Airflow
Hold-up Time	16mSec
Efficiency	75% Typical
Adjustment Range (V1 Only)	±5%
Ripple / Noise, max	1% pk-pk max
Line Regulation	Max ±0.2%
Load Regulation @ 60% ±40% Full Load	
V1	±3% max
V2-V4	±5% max
Cross Regulation @ 60% ± 40% Full Load	
V1: Change in V2 - V4	±0.5%
V2 - V4: Change in V1 @ 75 ±25% F/L	±5% max
Overvoltage Protection (V1 Only)	>130% (Latch Off)
Power Limit	>120% (Auto-Recovery)
Overshoot (all outputs)	10% max
Response Time	500 µSec (25-75% step load)
Switching Frequency	60KHz (typical)

ENVIRONMENTAL

Operating Temp. Range	-20°C to +50°C (Full Load)
	Consult factory for -40°C Guaranteed Start-Up and Industrial Temperature Range options
Output Current Derating	2.5%/°C, 50°C to 70°C
Storage Temp. Range	-40°C to + 85°C
Humidity	5% to 95%, Non-Condensing
MTBF, Demonstrated	>500,000 Hours
Cooling	30 cfm Airflow for Full Power
Immunity	EN61000-4-2: -3; -4; -5; -6; -8; -11
Altitude	10,000 feet

PHYSICAL SPECIFICATIONS

Case Dimensions	8.00 x 4.50 x 2.00" / 203.2 x 114.3 x 50.8mm
Weight	3.15 lbs. (1.43 kg.)
Vibration from 10 - 55Hz	1.0G Peak
	(3 orthogonal axes @ 1 octave/min, 5 minute dwell @ 4 major resonances)

SAFETY STANDARDS

UL60950-1 2nd Ed., EN60950-1 2nd Ed., CB REPORT (IEC 60950-1), CE MARK (LVD)

EMI STANDARDS

FCC Class B & VDE Class B, CISPR 22: EN 55022 Class B

OUTLINE DRAWING

CONNECTOR 1

Terminal Blocks, 9.5mm pitch
 PIN1.....LINE
 PIN2.....NEUTRAL
 PIN3.....GND

CONNECTOR 2 (single output)

Terminal Blocks, 9.5mm pitch
 PIN1 V1
 PIN2 V1
 PIN3 V1
 PIN4 V1
 PIN5 RET
 PIN6 RET
 PIN7 RET
 PIN8 RET

CONNECTOR 2 (multi-output)

PIN1 V1
 PIN2 V1
 PIN3 RET
 PIN4 RET
 PIN5 V2
 PIN6 V3
 PIN7 V4
 PIN8 +V4

CONNECTOR 3

MOLEX 22-27-2061 or equivalent
 Mates with MOLEX 22-01-3067
 PIN1.....+SENSE
 PIN2.....-SENSE
 PIN3.....RC
 PIN4.....AC FAIL
 PIN5.....RTN
 PIN6.....PG

