

**DCMOD® AJ-040D**  
**DC INPUT / ITE APPROVED**  
**40 WATT POWER PLATFORM**

3.6 x 2.5 x 1.00" | 91.44 x 63.5 x 25.4mm



### DESCRIPTION

UNIPOWER's DCMOD® AJ-040D SERIES is a 40 Watt DC Input Power Supply platform with both standard and configurable models featuring 12, 24 or 48VDC inputs and output voltage(s) that can be quickly configured to order while maintaining all international safety approvals.

These power supplies are available in single or triple output configurations with outputs ranging from 1.5 to 48 VDC. The AJ-040D feature a high-density footprint; 24 or 48VDC Input ranges; international safety approvals; Class B emissions; and -20 ~ +70°C operation (see derating).

DCMOD® UPGRADES include a multitude of output voltage configurations, extended temperature operating range, attached wire harnesses and much, much more. All these modifications are available without any impact on safety approvals to reduce both development cost and time to market.

### FEATURES

- ◆ 12V, 24V or 48V DC Input
- ◆ High-Density 3.6" x 2.5" Footprint
- ◆ 1 or 3 Outputs configurable from 1.5-48VDC
- ◆ International Safety Approvals
- ◆ >500k Hours MTBF, Demonstrated
- ◆ Optional -40°C Guaranteed Start-Up
- ◆ Double Sided PC Board



Contact UNIPOWER to discuss  
your application and define  
the right part number for your  
specific application:

Tel: +1-954-905-1070

Email: [the.power.solution@unipowerco.com](mailto:the.power.solution@unipowerco.com)



**FIVE YEAR WARRANTY**

### INTERNATIONAL STANDARDS

UL/cUL 60950-1 2nd Ed.  
EN60950-1 2nd Ed.  
CB Report, IEC60950-1  
CE Mark (LVD)

[www.unipowerco.com](http://www.unipowerco.com)

NORTH AMERICA CALL: +1-954-905-1071 • LATIN AMERICA CALL: +1-954-905-1078 • EUROPE CALL: +44 1903 768200

For the AC input version see [EASMOD AJ-040U](#) datasheet

For the Medical Approved version see [MEDIMOD AJ-040UM](#) datasheet

**"IF WHAT YOU SEE IS WHAT YOU DON'T WANT, IT CAN EASILY BE CHANGED."** The DCMOD® family of switching power supplies has been designed with two precepts; (1) the laws of physics are immutable, and (2) the satisfaction of customer requirements and needs is paramount.

A host of modifications, only some of which are listed below, can and will be performed on products for customer programs requiring as few as 250 units per year. These "mods" are available at nominal premium (if any), normally without non-recurring engineering costs (although a one time documentation fee may be incurred), and usually with all safety agency approvals in place. This minimizes both product development cost and new product time to market. Effectively, DCMODs® allow small program requirements the luxury of costly custom power supply designs.

**TYPICAL MODIFICATIONS**

- Unique Output Combinations from 1.5 to >48 volts
- Low Output Ripple and Noise
- Extended Temperature Operating Range
- -40°C Start-Up
- Zero Load Operation

**FLEXIBLE OUTPUT CONFIGURATION GUIDELINES**

with 12, 24 or 48VDC Input and -20-50°C Operation

**Single Output Capabilities**

OUTPUT CURRENT	1.5~3.3V	5V	12V	15V	24V	48V
MINIMUM	0A	0A	0A	0A	0A	0A
CONVECTION <sup>(3)</sup>	6A	6A	2.5A	2A	1.3A	0.6A
15 CFM AIR <sup>(4)</sup>	8A	8A	3.3A	2.6A	1.7A	0.8A
PEAK <sup>(5)</sup>	9.5A	9.5A	4A	3.3A	2.1A	1A

**Multiple Output Capabilities**

OUTPUT	DC OUTPUT	MIN	CON <sup>(3)</sup>	AIR <sup>(4)</sup>	PEAK <sup>(4, 5)</sup>
V1	1.5 ~ 48V <sup>(7)</sup>	0.40A <sup>(2, 12)</sup>	4.0A	5.0A	6.0A
V2	1.5 ~ 48V <sup>(8)</sup>	0.10A <sup>(2, 12)</sup>	1.0A	1.2A	1.5A
V3	1.5 ~ 48V <sup>(8)</sup>	0.08A <sup>(2, 12)</sup>	0.8A	1.0A	1.2A

(1) Full power out on V3 with minimal V1 and V2 loading—Option.  
 (2) 10% minimum load for stated regulation on multiple O/P units.  
 (3) Convection cooling.  
 (4) 15 CFM forced air cooling conditions.  
 (5) 30 seconds maximum duration.  
 (6) Most output combinations from 1.5 to 48+ Volts possible; up to maximum rated Current / Power...Consult UNIPOWER.

(7) Specify 0.1V increments.  
 (8) Specific output voltage is current dependent.  
 (9) Regulation may degrade under some output Consult UNIPOWER.  
 (10) Consult UNIPOWER for Model #.  
 (11) For outputs >48 Volts, consult UNIPOWER.  
 (12) 10% minimum of marked rating.

**Contact UNIPOWER to discuss your application and define the right part number for your specific application:**

**Call: +1-954-905-1070 • Email: [the.power.solution@unipowerco.com](mailto:the.power.solution@unipowerco.com)**

For the AC input version see [EASYMOD AJ-040D](#) datasheet | For the Medical Approved version see [MEDIMOD AJ-040UM](#) datasheet.

# SPECIFICATIONS

Typical at Nominal Line, Full Load and 25°C Unless Otherwise Noted.

### INPUT

Input Voltage Range Options.....9-18, 18-36 or 36-72 VDC  
 Input Current .....2A @ 48VDC / 3A @ 24VDC max / 6A @ 12VDC  
 Fusing.....4A @ 48VDC / 8A @ 24VDC / 10A @ 12VDC

### OUTPUT

Output Power .....30W Convection / 40W with 15 CFM Airflow  
 Efficiency.....70% Typical  
 Adjustment Range (V1 Only).....±5%  
 Ripple / Noise, max.....1% pk-pk max  
 Line Regulation.....Max ±0.2%  
 Load Regulation @ 60% ±40% Full Load  
     V1.....±3% max  
     V2-V3.....±5% max  
 Cross Regulation @ 60% ± 40% Full Load  
     V1: Change in V2 - V3.....±0.5%  
     V2 - V3: Change in V1 @75 ±25% F/L.....±5% max  
 Overvoltage Protection (V1 Only).....>125% (Latch Off)  
 Power Limit .....>120% (Auto-Recovery)  
 Overshoot (all outputs).....10% max  
 Response Time.....500 µSec (25-75% step load)  
 Switching Frequency.....60KHz (typical)

### ENVIRONMENTAL

Operating Temp. Range .....-20°C to +50°C (Full Load)  
 Consult factory for -40°C Guaranteed Start-Up  
 and Industrial Temperature Range options  
 Output Current Derating .....2.5%/°C, 50°C to 70°C  
 Storage Temp. Range .....-40°C to + 85°C  
 Humidity.....5% to 95%, Non-Condensing  
 MTBF, Demonstrated .....>500,000 Hours  
 Cooling .....15 CFM Airflow for Full Power  
 Altitude.....10,000 feet

### PHYSICAL SPECIFICATIONS

Case Dimensions .....3.60 x 2.48 x 1.00" / 91.5 x 63.0 x 25.4mm  
 Weight .....0.38 lbs. (0.17 kg.)  
 Vibration from 10 - 55Hz .....1.0G Peak  
 (3 orthogonal axes @ 1 octave/min, 5 minute dwell @ 4 major resonances)

### SAFETY STANDARDS

UL60950-1 2nd Ed., EN60950-1 2nd Ed., CB REPORT (IEC 60950-1),  
 CE MARK (LVD)  
 (not including 12VDC input models)

### EMI STANDARDS

FCC Class A & VDE Class A, CISPR 11; EN 55011 Class A  
 (Class B optional, consult factory)

## OUTLINE DRAWING

### CONNECTOR 1

(MOLEX#09-65-2038 OR EQUIVALENT;  
 MATING CONNECTOR= MOLEX#09-50-3031)  
 PIN1.....-VIN  
 PIN2.....Key  
 PIN3.....+VIN

### CONNECTOR 2 (single output)

(MOLEX#09-65-2068 OR EQUIVALENT;  
 MATING CONNECTOR= MOLEX#09-50-3061)  
 PIN1.....NC  
 PIN2.....RET  
 PIN3.....RET  
 PIN4.....V1  
 PIN5.....V1  
 PIN6.....NC

### CONNECTOR 2 (multi-output)

(MOLEX#09-65-2068 OR EQUIVALENT;  
 MATING CONNECTOR= MOLEX#09-50-3061)  
 PIN1.....V2  
 PIN2.....RET  
 PIN3.....RET  
 PIN4.....V1  
 PIN5.....V1  
 PIN6.....V3

