

120 Watts, Four Isolated Outputs
Unusual Output Combination
Arctic & Desert Operation
Field Communications Application
Custom Board Orientation
Reduced Chassis Height & Width



S4120 SOLUTIO CUSTOM



KEY SPECIFICATIONS

 Input Range
 85-264VAC

 Input Frequency
 47-63Hz

 Output Power
 120 Watts

 Efficiency
 85%

All Outputs Isolated

Holdup Time 20mS

Cooling 15CFM, Application Provided

Control Signals AC OK, DC OK, Temperature OK, Remote ON/OFF

Safety Standards UL60950-1, EN60950-1

EMI, Conducted & Radiated FCC Part 15 Class B, EN55022 Class B

Reliability In Excess of 300,000 Hours

Mechanical 1.45" H x 2.9" W x 5.0" D - U-Channel

UNIPOWER's Custom Product Team is highly experienced in working with customers from the early stages of spec definition through the actual development and production of one-of-a-kind power solutions.

Custom products require focus from concept through production. **UNIPOWER's** Custom Products Team is staffed with project engineers, technicians, manufacturing and quality personnel totally dedicated to meeting our customers' expectations. Our rapid response team is skilled at quickly developing custom products from **UNIPOWER's** broad base of proven, standard power circuits and components.

es4120-ds-revb-0714.ai

www.unipowerco.com



UNIPOWER NORTH AMERICA

3900 Coral Ridge Drive, Coral Springs, Florida 33065, USA Tel: +1-954-346-2442 . Fax: +1-954-340-7901 . sales-northamerica@unipowerco.com

UNIPOWER EUROPE

Parkland Business Centre, Chartwell Road, Lancing, BN15 8UE, ENGLAND Tel: +1-954-346-2442 . Fax: +1-954-340-7901 . sales-europe@unipowerco.com