



- CO



KEY SPECIFICATIONS

Input +24 or -48VDC

Capacity 150 Amps

Loads 6, Breaker Protected

Breakers 6, Magnetic, Toggle Type

EMI Filtered, Freq. 25-300Mhz

Input Connector Compression

Output Connectors 6, D-Sub

Form Factor 1RU, 19-inch

Mechanical 13.8" Deep

Galvanised Steel

Front Panel Custom Overlay

Application Type Cabinet

UNIPOWER's Custom Product Team is highly experienced in working with customers from the early stages of spec definition through the actual development and production of one-of-a-kind power solutions.

Custom products require focus from concept through production. **UNIPOWER's** Custom Products Team is staffed with project engineers, technicians, manufacturing and quality personnel totally dedicated to meeting our customers' expectations. Our rapid response team is skilled at quickly developing custom products from **UNIPOWER's** broad base of proven, standard power circuits and components.

es8547-ds-revb-0714.ai

www.unipowerco.com



UNIPOWER NORTH AMERICA

3900 Coral Ridge Drive, Coral Springs, Florida 33065, USA Tel: +1-954-346-2442 . Fax: +1-954-340-7901 . sales-northamerica@unipowerco.com

UNIPOWER EUROPE

Parkland Business Centre, Chartwell Road, Lancing, BN15 8UE, ENGLAND Tel: +1-954-346-2442 . Fax: +1-954-340-7901 . sales-europe@unipowerco.com