

RELAY RACKS

ALUMINUM

19" or 23" | 24RU to 58RU

FEATURES

- ◆ Universal junction hole pattern matches most manufacturers racks.
 - ◆ #12-24 panel mounting holes.
 - ◆ Conformance to EIA/ECA-310-E.
 - ◆ Load Rating: 1200 lbs. (544kg) weight capacity when evenly distributed for the height of the rack (84" (2.13m) and shorter).
 - ◆ Permanently stamped rack mount unit (RMU) markings included.
 - ◆ Packaged unassembled in protective carton suitable for parcel shipment.
 - ◆ Assembles in about ten (10) minutes using standard hand tools.
 - ◆ Includes thirty (30) dog point combo head [Phillips and flat blade] mounting screws.
 - ◆ Double sided universal [5/8" (16mm), 5/8" (16mm) , 1/2" (13mm)] mounting spacing.
 - ◆ Twin top angles for rigidity.
 - ◆ Tapped assembly holes eliminate the need for nuts and simplifies assembly and squaring.
 - ◆ Material: Aluminum
 - ◆ Finish: Brushed (AL) uprights with Silver Telco Gray Powder Coat (TG) or Flat Black Powder Coat (FB)
- Other finishes are available upon request

TWO-YEAR WARRANTY



STANDARD SIZES

HEIGHT ins. (m)	RACK UNITS	PANEL WIDTH	PART NUMBER
48 (1.2)	24RU	19"	170.0120.048
72 (1.8)	38RU		170.0120.072
84 (2.1)	45RU		170.0120.084
96 (2.4)	51RU		170.0120.096
108 (2.7)	58RU		170.0120.108
48 (1.2)	24RU	23"	170.0121.048
72 (1.8)	38RU		170.0121.072
84 (2.1)	45RU		170.0121.084
96 (2.4)	51RU		170.0121.096
108 (2.7)	58RU		170.0121.108

Specify finish at time of order:

- Brushed (AL)
- Telco Gray Powder Coat (TG)
- Flat Black Powder Coat (FB)

Other heights available to special order, please consult sales.

DIMENSIONS

	19" (482mm)	23" (594mm)
'A' Overall Height	36" - 108" (914mm - 2743mm)	36" - 108" (914mm - 2743mm)
'B' Overall Width	20 ⁵ / ₁₆ " (516mm)	24 ⁵ / ₁₆ " (617mm)
'C' Panel Mounting	18 ⁵ / ₁₆ " (465mm)	22 ⁵ / ₁₆ " (567mm)
'D' Usable Inside Width	17 ³ / ₄ " (451mm)	21 ³ / ₄ " (552mm)
'E' Base Anchor Spacing	16" (406mm)	20" (508mm)

Universal Spacing [⁵/₈" (16mm), ⁵/₈" (16mm), ¹/₂" (13mm)]

PART NUMBER	'A' HEIGHT ins. (mm)	'F' SPACING ins. (mm)	MOUNTING SPACES	SHIPPING WEIGHT Lbs. (kg)
170.0120.048	48 (1219)	3 ⁷ / ₁₆ (87)	24	24.0 (10.9)
170.0120.072	72 (1829)	27 ⁷ / ₁₆ (697)	38	27.5 (12.5)
170.0120.084	84 (2133)	39 ⁷ / ₁₆ (1001)	45	30.0 (13.6)
170.0120.096	96 (2438)	51 ⁷ / ₁₆ (1306)	51	31.5 (14.3)
170.0120.108	108 (2749)	54 ³ / ₁₆ (1376)	58	33.5 (15.2)
170-0121-048	48 (1219)	3 ⁷ / ₁₆ (87)	24	26.5 (12.0)
170-0121-072	72 (1829)	27 ⁷ / ₁₆ (697)	38	30.0 (13.6)
170-0121-084	84 (2133)	39 ⁷ / ₁₆ (1001)	45	32.0 (14.5)
170-0121-096	96 (2438)	51 ⁷ / ₁₆ (1306)	51	34.0 (15.4)
170-0121-108	108 (2749)	54 ³ / ₁₆ (1376)	58	36.0 (16.8)

Junction Hole Pattern for 84" tall rails

