



120V INPUT, 50-60Hz

Rated Current (Amps)	Max. Current (Amps)	kVA	Output Voltage Range	Type No.	MTG	Notes	Chokes Req'd for Parallel OP *	Net Weight (lbs)	Ship Weight (lbs)	Dimensions (inches)		
										W	H	D
2.0	2.6	0.31	0-140	W2M †	ENCL.			4	9	4.125	5.562	4.375
2.4	3.1	0.37	0-140	W2	OPEN			3	4	3.250	3.687	3.937
5.0	6.5	0.78	0-140	W5M † *	ENCL.			7	13	4.875	6.562	4.375
6.0	7.8	0.94	0-140	W5 † ‡	OPEN			6	8	4.500	4.937	3.937
7.1	9.2	1.1	0-120	W5LM	ENCL.	60Hz ONLY		7	13	4.875	6.562	4.375
8.5	11.0	1.32	0-120	W5L † ‡	OPEN	60Hz ONLY		7	8	4.500	4.937	4.687
8.5	11.0	1.32	0-140	W8	OPEN			8	9	4.500	4.937	4.437
10.0	13.0	1.56	0-120	W8L ‡	OPEN	60Hz ONLY		8	12	4.500	4.937	4.437
10.0	13.0	1.56	0-140	W10 †	OPEN			12	13	5.750	6.312	3.937
10.0	13.0	1.56	0-140	W10M † *	ENCL.			15	17	6.750	9.500	5.250
14.2	18.4	2.2	0-120	W5LG2M	ENCL.	60Hz ONLY	1	15	23	5.125	6.750	8.125
17.0	22.0	2.6	0-120	W5LG2	OPEN	60Hz ONLY	1	14	16	4.500	4.937	8.000
17.0	22.0	2.6	0-140	W8G2	OPEN		1	16	19	4.500	4.937	9.312
20.0	26.0	3.12	0-140	W20 † ‡	OPEN			21	24	7.500	8.062	4.625
20.0	26.0	3.12	0-140	W20M †	ENCL.			24	29	8.625	11.937	5.375
20.0	26.0	3.1	0-120	W8LG2	OPEN	60Hz ONLY	1	17	19	4.500	4.937	9.312
21.3	27.6	3.3	0-120	W5LG3M	ENCL.	60Hz ONLY	3	22	32	5.125	6.750	12.250
25.5	33.0	4.0	0-120	W5LG3	OPEN	60Hz ONLY	3	20	22	4.500	4.937	12.125
25.5	33.0	4.0	0-140	W8G3	OPEN		3	25	27	4.500	4.937	13.937
30.0	39.0	4.7	0-120	W8LG3	OPEN	60Hz ONLY	3	25	27	4.500	4.937	13.937
40.0	52.0	6.2	0-140	W20G2M	ENCL.		1	48	56	9.000	12.062	9.375
40.0	52.0	6.2	0-140	W20G2	OPEN		1	43	48	7.500	8.062	9.187
60.0	78.0	9.4	0-140	W20G3M	ENCL.		3	71	82	9.000	12.062	13.937
60.0	78.0	9.4	0-140	W20G3	OPEN		3	65	71	7.500	8.062	13.750

† UL Listed * UL Recognized ‡ CSA Approved

240V INPUT, 50-60Hz

Rated Current (Amps)	Max. Current (Amps)	kVA	Output Voltage Range	Type No.	MTG	Notes	Chokes Req'd for Parallel OP *	Net Weight (lbs)	Net Weight (lbs)	Dimensions (inches)		
										W	H	D
2.0	2.6	0.62	0-280	W5H †	OPEN			6	8	4.500	4.934	3.964
2.0	2.6	0.62	0-280	W5HM †	ENCL.			7	13	4.875	6.562	4.375
2.4	3.1	0.74	0-280	W2G2	OPEN	SERIES		7	9	3.250	6.562	7.964
4.0	5.2	1.25	0-280	W10H †	OPEN			11	12	5.750	3.687	4.687
4.0	5.2	1.25	0-280	W10HM	ENCL.			14	17	6.750	9.500	5.250
5.0	6.5	1.56	0-280	W5G2M	OPEN	SERIES		15	23	5.125	6.750	8.125
6.0	7.8	1.87	0-280	W5G2 ‡	OPEN	SERIES		14	15	4.500	4.937	8.000
8.0	10.4	2.5	0-280	W20H	OPEN			20	23	7.500	8.062	4.625
8.0	10.4	2.5	0-280	W20HM † *	ENCL.			23	28	8.625	11.934	5.375
8.5	11.0	2.64	0-280	W8G2	OPEN	SERIES		16	19	4.500	4.934	9.312
10.0	13.0	3.12	0-280	W8LG2	OPEN	SERIES 60HZ		17	19	4.500	4.934	9.312
10.0	13.0	3.12	0-280	W10G2	OPEN	SERIES		25	27	5.750	6.934	9.500
10.0	13.0	3.12	0-280	W10G2M	ENCL.	SERIES		29	34	7.125	9.687	4.125
16.0	20.8	4.99	0-280	W20HG2	OPEN	PARALLEL	1	41	46	7.500	8.062	9.375
20.0	20.8	4.99	0-280	W20HG2M	ENCL.	SERIES		45	54	9.000	12.062	9.187
20.0	26.0	6.24	0-280	W20G2	OPEN	SERIES		43	48	7.500	8.062	9.187
20.0	26.0	6.24	0-280	W20G2M	ENCL.			48	56	9.000	12.062	9.375

† UL Listed * UL Recognized ‡ CSA Approved

480V INPUT, 50-60Hz

Rated Current (Amps)	Max. Current (Amps)	kVA	Output Voltage Range	Type No.	MTG	Notes	Chokes Req'd for Parallel OP *	Net Weight (lbs)	Net Weight (lbs)	Dimensions (inches)		
										W	H	D
2.0	2.6	1.24	0-560	W5HG2	OPEN	SERIES		13	15	4.500	4.937	12.125
2.0	2.6	1.24	0-560	W5HG2M	ENCL.	SERIES		15	23	5.125	6.750	12.250
4.0	5.2	2.5	0-560	W10HG2	OPEN	SERIES		24	27	5.750	6.312	14.000
4.0	5.2	2.5	0-560	W10GH2M	ENCL.	SERIES		29	33	7.125	9.687	14.187
8.0	10.4	5	0-560	W20HG2	OPEN	SERIES		41	46	7.500	8.062	13.750
8.0	10.4	5	0-560	W20HG2M	ENCL.	SERIES		45	54	9.000	12.062	13.937